

FLO-KWIP

ROAD RAMPS



FLO-KWIP Road Ramps are designed to provide safe transfer of pumped water across roadways and footpaths, safely and with minimal disruption to traffic flow.

Certificate Number: PE-TKP-003

www.toolkwippumps.com



FLO-KWIP



SPECIFICATIONS

Single Wheel Axle = Loads up to 8.2 Tonnes
Dual Wheel Axle = Loads up to 11 Tonnes

This exceeds the maximum NHVR axle weight limits, meaning any truck on the road will be able to safely drive over the ramp.

FEATURES

- ▶ Certified load rated
- ▶ Pressure rated to 3 BAR
- ▶ Designed for minimal water friction losses
- ▶ Dedicated Load Rated Lifting Points
- ▶ Hold down/retention points
- ▶ Safety Paint Marking to Australian Standards
- ▶ Customisable flange size
- ▶ Easy and Fast to install
- ▶ Transportable
- ▶ Stackable
- ▶ Available with 4", 6" or 8" connections

TECHNICAL SPECIFICATIONS

Overall Width	3980mm*
Ramp Width	2960mm
Ramp Height	78mm
Total Height	435mm
Length	1182mm

*Width is flange to flange and does not include Bauer couplings



DISTRIBUTED BY:



HEAD OFFICE:
8-10 Parkhurst Drive
Knoxfield VIC 3180
P: 03 8805 0500

NSW OFFICE
65 Seaton Street
Armidale, NSW 2350
P: 02 7251 3499

QLD OFFICE
27 Container Street
Tingalpa, QLD 4173
P: 07 3523 5777

www.toolkwippumps.com

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE. PHOTOS AND ILLUSTRATIONS DO NOT ALWAYS SHOW STANDARD VERSIONS OF MACHINES.
THE ABOVE INFORMATION IS A GENERAL DESCRIPTION ONLY, ALL INFORMATIONS ARE SUPPLIED WITHOUT LIABILITY.